



Management
System
ISO 9001:2015
www.tuv.com
ID: 910522371

Certificado de Calidad

IT020305 rev.01

N° NN-21044

Industrias Nelson
Av. Rivadavia 12140 – Ciudadela – Buenos Aires
info@industriasnelson.com.ar / www.industriasnelson.com.ar
T.E. 0800-333-4237

Descripción	Código	Certificado
CONECTOR RECTO 5/8" OD X 3/4"	68S1008	AA-764
Componentes	Material	Certificado
BARRA HEXAGONAL 28.5MM	AISI 316I	AA-764

Protocolo de ensayo :

Tipo		Presión de trabajo	Estado	Presión de prueba	Estado	Tiempo
Hidráulico	1	3.000 PSI	Ok	5.000 PSI	Ok	60 segundos

Dimensional:

Se controlaron las roscas con el calibre correspondientes dando como resultado satisfactorio. Se controlaron también la rugosidad superficial y las dimensiones generales dando un resultado satisfactorio.

Visual/Funcional:

Se controlaron la porosidad, rebabas, ensamblado, terminación superficial y su función mecánica dando como resultado: satisfactorio

Observaciones :

Se certifica que las piezas descritas fueron construidas de acuerdo a lo indicado en nuestros estándares internos, que se cumplen de acuerdo a un sistema de Gestión de Calidad certificado ISO 9001:2015, manteniendo en archivo los certificados correspondientes a cada material.

Firma: **INDUSTRIAS NELSON S.A.**



江苏晨明不锈钢材料有限公司 厂址: 中国江苏兴化市戴南镇裴马工业园						编码:					
 JIANGSU CHENMING STAINLESS STEEL CO.,LTD ADD:Peima Industrial park,Dainan town ,Xinghua city,Jiangsu Prov.,CN 225721						T:+86-523-83982888 F:+86-523-83786818 info@chenmingstainless.com www.chenmingstainless.com					
CERTIFICATE OF SPECIFICATION											
ACCORDING TO EN 10204:2005											
CONSIGNEE: XXXXXXXXXX CUIT 30-71534329-7 RUTA PANAMERICANA KM 31,200 COLECTORA OESTE (1617) EL TALAR, BUENOS AIRES, ARGENTINA						Certificate No.: CM2022-JND-ID221220 Date of Issue: 20 DEC,2022 DOCUMENTARY CREDIT NUMBER: INV No.: CMS20221220					
DELIVERY CONDITION		LENGTH REQUEST		TRADE MARK		ORIGINAL		STANDARDS		METLING PROCESS	
A		6 MTS		CHENMING		CHINA		ASTM A276/A484		EF/AOD/MEMS.	
STAINLESS BRIGHT ROUND BAR AND HEX BAR											
ORDER DETAILS						MECHANICAL PROPERTIES (Testing methods as per ASTM A370)					
SIZE (MM or IN)	GRADE	SHAPE	NET WEIGH (KGS)	FINISHING	HEAT TREATMENT °C	HARDNESS (HBN)	0.2% PROOF STRENGTH MPA	TENSILE STRENGTH MPA	ELONGATION %	REDUCTION OF AREA %	HEAT No.
38.1MM	304L	ROUND BAR	435	BRIGHT	1050	172	468	669.0	43	62	HT2212201
50.8MM	304L	ROUND BAR	779	BRIGHT	1050	172	468	669.0	43	62	HT2212201
63.5MM	304L	ROUND BAR	756	BRIGHT	1050	169	470	672.0	41	60	HT2212202
76.2MM	304L	ROUND BAR	656	BRIGHT	1050	169	470	672.0	41	60	HT2212202
88.9MM	304L	ROUND BAR	594	BRIGHT	1050	169	470	672.0	41	60	HT2212202
101.6MM	304L	ROUND BAR	775	BRIGHT	1050	169	470	672.0	41	60	HT2212202
9.52MM	316L	ROUND BAR	252	BRIGHT	1050	213	550	785.0	45	67	HT2212203
12.7MM	316L	ROUND BAR	359	BRIGHT	1050	213	550	785.0	45	67	HT2212203
15.88MM	316L	ROUND BAR	523	BRIGHT	1050	182	489	699.0	45	65	HT2212204
19.05MM	316L	ROUND BAR	773	BRIGHT	1050	182	489	699.0	45	65	HT2212204
22.22MM	316L	ROUND BAR	968	BRIGHT	1050	182	489	699.0	45	65	HT2212204
25.4MM	316L	ROUND BAR	1535	BRIGHT	1050	182	489	699.0	45	65	HT2212204
28.6MM	316L	ROUND BAR	987	BRIGHT	1050	182	489	699.0	45	65	HT2212204
31.7MM	316L	ROUND BAR	721	BRIGHT	1050	182	489	699.0	45	65	HT2212204
35MM	316L	ROUND BAR	507	BRIGHT	1050	182	489	699.0	45	65	HT2212204
50.8MM	316L	ROUND BAR	589	BRIGHT	1050	182	489	699.0	45	65	HT2212204
63.5MM	316L	ROUND BAR	764	BRIGHT	1050	180	483	690.0	44	64	HT2212205
76.2MM	316L	ROUND BAR	446	BRIGHT	1050	180	483	690.0	44	64	HT2212205
14.3MM	316L	HEX BAR	2552	BRIGHT	1050	217	545	778.0	43	65	HT2212206
15.88MM	316L	HEX BAR	1081	BRIGHT	1050	211	538	768.0	41	63	HT2212207
17.4MM	316L	HEX BAR	1621	BRIGHT	1050	211	538	768.0	41	63	HT2212207
20.63MM	316L	HEX BAR	1581	BRIGHT	1050	211	538	768.0	41	63	HT2212207
22.22MM	316L	HEX BAR	2539	BRIGHT	1050	211	538	768.0	41	63	HT2212207
28.6MM	316L	HEX BAR	1068	BRIGHT	1050	211	538	768.0	41	63	HT2212207
CHEMICAL ANALYSIS (Testing methods as per ASTM A751)											
HEAT NO.:	% C	% Si	% Mn	% P	% S	% Cr	% Ni	% Mo	% Cu	-	
HT2212201	0.021	0.46	1.03	0.0031	0.002	18.11	8.04	-	0.18		
HT2212202	0.022	0.44	1.05	0.0029	0.002	18.13	8.04	-	0.2		
HT2212203	0.014	0.47	1.03	0.0026	0.001	16.65	10.16	2.23	-		
HT2212204	0.016	0.46	1.02	0.0028	0.001	16.57	10.21	2.18	-		
HT2212205	0.017	0.45	1.01	0.0027	0.002	16.68	10.19	2.21	-		
HT2212206	0.015	0.45	1.02	0.0027	0.001	16.74	10.21	2.22	-		
HT2212207	0.019	0.48	1.03	0.0028	0.002	16.65	10.22	2.15	-		
ULTRASONIC TESTING -NDT						REMARKS					
						*Free from radioactivity-verified through Gamma Ray Spectrometer *Free from mercury contamination *No welding has been performed on the material *Third-party heat treatment furnace calibrated as per Annexure M *Visual & Dimensional inspection -OK					
We confirmed that the material is manufactured & supplied in accordance to the Purchase Order											
SIGNATURE: _____											
CHENMING STAINLESS for better future											